



The Top-speed Professional for Colour in A4.

The FS-C5400DN delivers an astounding 35 pages per minute in vibrant colour output and fulfils the highest user-demands with the option for a total of 6 paper trays, for flexible paper handling. Add this to its compact design, Kyocera reliability, and long-life components; the FS-C5400DN is perfect for office use or in-house production.

- ▶ Up to 35 pages per minute A4 in colour and monochrome
- ▶ Up to 9,600 x 600 dpi printing quality with multi-bit technology
- ▶ Standard duplex unit for double-sided printing
- ▶ Standard USB and Network Connectivity
- ▶ Amazing 300,000 page drum life
- ▶ 150-sheet multi-purpose tray
- ▶ 500-sheet universal cassette
- ▶ Exceptionally low printing costs in its class





The FS-C5400DN includes:

PRESCRIBE IIC

With the Kyocera page design and control language PRESCRIBE IIC, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KYOCERA NetViewer

The KYOCERA Net Viewer enables complete monitoring and control of all ECOSYS printers and digital Kyocera multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

Our Unique Printing Technology

ECOSYS stands for ECOlogy, ECONomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables.

The cartridge-free system means that only the toner has to be replaced regularly, and the drum unit every 300,000 prints. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

General
Technology Kyocera ECOSYS Colour Laser Printer
Engine speed Up to 35 pages per minute in A4 in colour and mono
Resolution 600 x 600 dpi Multi-Bit Technology for print quality of up to 9,600 x 600dpi
Duty cycle Max. 150,000 pages per month (A4)
Warm-up time Approx. 45 seconds from sleep mode
Time to first page Approx. 8.0 seconds or less in monochrome Approx. 9.0 seconds or less in colour
Dimensions (W x D x H) 345 mm x 518 mm x 510 mm
Weight Approx. 35 kg (basic unit ready for operation)
Power source 220/240 V, 50/60 Hz
Power consumption Printing: 608 W Stand-by: 91 W Power-Saving: 10 W
Safety standards GS, TÜV, CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling
All paper capacities quoted are based on 80gsm paper, thickness of max 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.
Input capacity 150-sheet multi-purpose tray; 60–220 g/m ² ; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 138 mm – 216 x 356 mm) 500-sheet universal cassette; 60–120 g/m ² ; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm) Max. paper capacity incl. options: 2,650 sheets
Duplex unit Double-side printing: 60–120 g/m ² ; A4, A5, B5, Letter, Legal, Custom (140 x 210 mm – 216 x 356 mm)
Output capacity 500-sheet-face-down with paper full sensor

Controller
CPU PowerPC 750/733 MHz
Memory 256MB RAM, can be increased to 1,280MB RAM (single DIMM slot) as an option
Standard interface USB 2.0 (Hi-Speed), USB Host Interface Fast Ethernet (10/100 Base-TX for IPv4/IPv6)
Controller language PRESCRIBE IIC
Emulations PCL6, PCL5c, PostScript® 3 (KPDL 3), XPS (Windows Vista), PDF Direct Print, with automatic emulation sensing
Operating systems All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems
Fonts/barcodes 93 scalable fonts for PCL, 136 scalable fonts for PostScript®, 8 fonts for Windows Vista®, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
Integrated accounting 100 department codes

Consumables
TK-574K Toner-kit Micro-Particle toner black for 16,000 pages A4 in accordance with ISO/IEC 19798
TK-574C, TK-574M, TK-574Y Toner-kits Micro-Particle toner cyan, magenta, yellow for 12,000 pages A4 in accordance with ISO/IEC 19798 Capacity of starter toner is black 8,000 pages, and cyan, magenta, yellow is 6,000 pages each in accordance with ISO/IEC 19798 Maintenance Kit: MK-570 Installed every 300,000 pages

Options
PF-500 Paper feeder Max. 500 sheets; 60–120 g/m ² ; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)
PF-510 Multi-Media Feeder Max. 500 sheets; 60–220 g/m ² ; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm) Max. 4 x PF-500 or PF-510 feeders in any combination for a total of 2,650 sheet input
CA-500 Caster Kit If the FS-C5400DN is placed on the floor with 1 paper feeder or more, then the CA-500 must be installed

Memory upgrade DIMM-512P: 512MB extension Or DIMM-1GBP: 1GB extension 1 slot available for memory upgrade
CompactFlash®-Card 1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage
USB Flash Memory Supports direct printing of PDF, XPS, TIFF, JPEG files via USB Host Interface
HD-5A Hard Disk 40GB for forms, fonts, virtual mailbox and more

Warranty
2-year warranty as standard. Kyocera guarantees the drums and developers for 2 years or maximum 300,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.



Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Document Solutions Australia
Ph: 13 KYOCERA (596 2372)
www.KyoceraDocumentSolutions.com.au

KYOCERA Document Solutions New Zealand
Ph: 0508 KYOCERA (596 2372)
www.KyoceraDocumentSolutions.co.nz

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

